

Centurion[™] C5 Configurable Controller

The Centurion Configurable Controller is a control and monitoring system. Primarily designed for engine/electric motor-driven compressors, the Centurion is well suited for many control applications using standard configurations to save money and reduce training. Additionally, we can custom design a control package to meet exact specifications for a variety of applications.

The Centurion continuously monitors input signals and set points and commands outputs to maintain proper operation. When an out-of-limits event occurs, the controller will stop, shut down or control equipment to change conditions. The auto-start capabilities of the Centurion allow for start/stop based on parameters such as pressure set points or by digital signals.

The Centurion provides real-time data via communication ports to a connected display and/or supervisory system. This advanced system offers multiple options for remote communications and operation including HMIs, PLCs, PCs and SCADA systems. The industry standard MODBUS RTU protocol means greater support for a wide variety of communication equipment including radio and satellite communications systems.



Features

- Fully configurable control and monitoring system. Applications include reciprocating/screw compressors and pump systems.
- Expandable system to meet most three-to four-stage compressor applications.
- User configurability with Windows-based software allows the operator to point and click to implement standard processes. All I/O points can be custom configured.
- No programming experience required.
- Local and remote communications, MODBUS RTU via RS485/232/Ethernet.
- USB 1.1/2.0 support for laptops without a serial port.
- Upload/download capabilities for configurations and set points.
- Shut-down history list (Last 20 events).
- Event history list (Last 32 events).
- Active alarm list.
- 10 configurable maintenance timers.
- Run hourmeter.
- Support for no-flow totalization using lubricator pulses.
- Short cycle start protection / starts per hour (electric motor).
- Eight control loops, closed loop PID / open loop linear.
- Configuration templates provided for simple use.
- Configurations stored in non-volatile Flash memory.
- Set points stored in non-volatile EEPROM memory.
- CAN capable, to support electronic engines.
- Same core module for Centurion Configurable and Centurion Custom applications.
- View EICS and Centurion systems on one M-VIEW Touch screen display.
- Diagnostics that reduce troubleshooting.
- World-class certifications and harmonized international standards.
- Future-proof and backward compatible.
- All non-incendive inputs.
- Compressor Rod Load calculation, alarm and shutdown.

Basic Components

The Centurion consists of a display module, a main I/O module and optional expansion I/O module and choice of M-VIEW Series displays. No special cables are required. The Centurion is designed for use within a weatherproof enclosure only.

C5-1, Main I/O Module: Choose from
 Centurion Configurable applications
 Centurion Custom applications


(Optional) MX4-R2 Expansion I/O Module:

(Optional) MX5-R2 Expansion I/O Module:

Display: Choose from
 MV-5
 MV-7T
 MV-10T

C5-1 Main I/O Module


- Operating temperature: 40° to 185° F (-40° to 85° C)
- Power input: 10-30 VDC
- Configuration: PC-based Centurion Configuration Software
- Application firmware:
 - Standard offers a user-configurable experience
 - Centurion Custom option offers highly customized applications.Centurion programmable - integrates with Rockwell Automation Processors as I/O module to write IEC 61131-3 logic (Ladder Logic, Structured Text, Function Block Diagram).
- All I/O options individually software selectable. No jumpers required.
- 12 Analog inputs*:
 - 0-24 mA or 0-5 VDC, 15-bit hardware
 - 4 configurable for resistive potentiometer measurement
- 32 Digital inputs*:
 - NO or NC (active high/active low) non-incendive
 - Optically isolated DC digital inputs (active high/active low) with LED indicators
 - Polarity sense / wire fault detection on normally closed systems
 - Approved for use with general purpose switches in hazardous areas
- Eight temperature inputs*:
 - J or K Type Thermocouples, 3-wire
 - 100Ω Pt RTD temperature inputs
 - Open, short DC-, short DC+ wire fault detection
 - Cold junction compensation
- One magnetic pickup input/AC run signal:
 - 30 to 10 kHz, 4.5 VAC rms min, 120 VAC rms max.
- 10 digital outputs:
 - LED indicators:
 - 4 relay outputs, form C, dry contacts
 - 4 FET outputs (source)
 - 2 FET outputs (sink)
- Four analog outputs:
 - 4-20 mA, 16-bit hardware
- 11 Communication ports:
 - Two SERIAL RS232:
 - > Protocol: MODBUS RTU (slave)
 - Two SERIAL RS485:
 - > Protocol: MODBUS RTU (slave)
 - One USB: Host Type A (data log access, firmware updates)
 - One USB: Slave Type B (configuration/firmware updates)
 - Two CAN:
 - > One proprietary for FW Murphy hardware
 - > One reserved for J1939 Engine ECU
 - Two Ethernet 10/100 (DLR):
 - > Protocol: Modbus TCP/IP (slave)
 - > EtherNet/IP (CIP)
 - One WiFi: Optional
- Third-party approvals:
 - Class 1, Zone 2, AEx ec [ic] nC IIC T4 Gc, Ex ec [ic] nC IIC T4 Gc
 - ATEX /CE Zone 2
 - IECEx Zone 2



Expansion I/O Modules

MX4-R2 Expansion I/O Module

- Operating Temperature: 40° to 185° F (-40° to 85° C)
- Power input: 10-30 VDC
- Configuration: PC-based Centurion Configuration Software
- 18* thermocouple inputs: J or K Type thermocouples, 9* 3-wire 100Ω Pt RTD temperature inputs
- Open, short DC-, Short DC+ wire fault detection
- Cold junction compensation
- One magnetic pickup input / AC Run Signal: 4.5 VAC – 120 VAC, 30 Hz – 10 kHz
- Third-party approvals:
 - Class 1, Zone 2, AEx ec [ic] IIC T4 Gc, Ex ec [ic] IIC T4 Gc
 - ATEX /CE Zone 2
 - IECEx Zone 2



MX5-R2 Expansion I/O Module

- Operating temperature: 40° to 185° F (-40° to 85° C)
- Power input: 10-30 VDC
- Configuration: PC-based Centurion Configuration Software
- 24**Digital inputs:
 - NO or NC (active high/active low) non-incendive
 - Optically isolated DC digital inputs (active high/active low) with LED indicators
 - Polarity sense / wire fault detection on normally closed systems
 - Approved for use with general purpose switches in hazardous areas
- 8 std. config./ 10** analog inputs: 0-24 mA or 0-5 VDC, 15 bit hardware.
- 6 std. config./ 16** digital outputs: FET (sink).
- 4 analog outputs: 4-20 mA, 16 bit hardware.
- 1 magnetic pickup input* /AC Run Signal: 4.5 VAC -120 VAC, 30 Hz to 10 kHz
- Third-party approvals:
 - Class 1, Zone 2, AEx ec [ic] IIC T4 Gc, Ex ec [ic] IIC T4 Gc
 - ATEX /CE Zone 2
 - IECEx Zone 2



* Non-incendive.

** Applies only to Centurion™ Custom and Rockwell Automation® Processor configurations.

RTD=Resistive Temperature Device

M-VIEW Monochrome Display

- Operating temperature: -40° to 185° F (-40° to 85° C)
- Power input: 10-30 VDC
- Screen: 320 x 240 pixels, LCD display with backlight
- User interface: 12-key keypad set point entry, alarm acknowledgment, start, stop, reset, etc.
- Communications:
 - RS232-1/RS485-1 (MODBUS RTU master)
 - RS485-2 (MODBUS RTU slave)
 - 1 USB Slave Type B (firmware updates)
 - 1 USB Host Type A (reserved)
 - CAN x 2
 - >1 proprietary for FW Murphy Hardware
 - >1 reserved for J1939 engine ECU
- Customizable process screens (up to nine):
 - Line by line
 - Gage
 - Control loop
 - Generic register
- Built-in screens (examples):
 - Digital input status and polarity
 - Digital output status
 - Temperature input status/fault
 - Fault snapshot (mirror of line by line)
 - Alarm log
 - Event Log
- Third-party approvals:
 - Class 1, Division 2
 - ATEX Zone 2
 - IECEx Zone 2, IP66 (face)
 - Outdoor (face)




M-VIEW Touch Series Displays

- Operating temperature: 40° to 140° F (-20° to 60° C)
- Power input: 10-30 VDC
- Screen (sunlight readable):
 - M-VIEW-7, 800x480 pixels, 7" widescreen
 - M-VIEW-10, 640x480 pixels, 10.4" screen
- User interface: resistive analog touchscreen
- Communication interface
 - 2x RS232
 - 1x RS485
 - 2x USB host type A (file transfer, datalogging, USB device)
 - 1x USB slave (program/firmware updates)
 - 2 Ethernet 10/100 Base TX (RJ45)
- Communication protocols:
 - EtherNet/IP (CIP)
 - Modbus TCP/IP
 - Modbus RTU standard
 - 300 plus available, web server
- Third-party approvals:
 - Class 1, Division 2
 - ATEX Zone 2
 - IECEx Zone 2, IP66 (face)
 - Outdoor (face)




Dimensions


MV-5 Display




MV-7T Display



MV-10T Display



C5-1 Main Module



How to Order

- (1) Select a Centurion Configurable Controller
 - C5-1 Main Module
- (2) Specify expansion i/o modules (optional)
 - MX4-R2 or MX5-R2
- (3) Specify a display model
 - MV-5
 - MV-7T
 - MV-10T

The minimum system requirements:

- C5-1 Main I/O Module
- Display capable of MODBUS communications

The FW Murphy M-VIEW Series displays are highly integrated HMIs for use with the Centurion system and are recommended for most customers.

Some systems may require additional I/O which is available on the MX4-R2 or MX5-R2 expansion I/O modules.

Part Number	Description	Notes
Specify Model	C5-1, Centurion Controller (Main Module)	
	MV-5, (5 in. monochrome display)	
	MV-7T, (7 in. touch, full-color display)	Standard with auto sync to C5-1
	MV-10T, (10 in. touch, full-color display)	
50703852	MX4-R2 expansion I/O module	
50703853	MX5-R2 expansion I/O module	
50000774	Ignition noise (choke) filter	
00032696	C5-1 Plug kit	Printed replacement terminal plugs for main I/O module
00030867	MX4-R2 Plug kit	Printed replacement terminal plugs for MX4-R2 expansion I/O module
00030868	MX5-R2 Plug kit	Printed replacement terminal plugs for MX5-R2 expansion I/O module
50702313	Centurion configuration tool for user application setup	Centurion configuration tool is software for modifying sequence of operation, set points, timers, faults and displays for Centurion. Includes file transfer utilities for configuration and upgrades.